



Safety Data Sheet

STP Products Manufacturing Company

44 Old Ridgebury Road
Suite 300
Danbury, CT 06810
Tel. 1-203-205-2900

1. Product And Company Identification

Product Name: Armor All® FRESH fx™ Smoke X™ Aerosol - Midnight Air

Responsible Party: STP Products Manufacturing Company
44 Old Ridgebury Road
Suite 300
Danbury, CT 06810

Information Phone Number: +1 203-205-2900

Emergency Phone Number:

For Medical Emergencies, call 1-866-949-6465 / +1 303-389-1332 (Outside US and Canada)
For Transportation Emergencies, call 1-800-424-9300 (Chemtrec) +1-703-527-3887 for
Outside US and Canada (call collect)

SDS Date of Preparation: 07/24/2018

Product Use and Uses Advised Against: Automotive maintenance product – For consumer and professional use

2. Hazards Identification

GHS Classification:

Physical:	Health:
Flammable Aerosol Category 1 Gases Under Pressure: Compressed Gas	Eye Irritant Category 2A

GHS Label Elements:



Danger!

Statements of Hazard

Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes serious eye irritation.

Storage

Protect from sunlight. Do not exposure to temperatures exceeding 50°C / 122°F.
Store in a well-ventilated place.

Disposal

Dispose of contents and container in accordance with local and national regulations.

Precautionary Phrases

Prevention

Keep away from heat, sparks, open flames, and hot surfaces.
No smoking.
Do not spray on an open flame or other ignition source.
Pressurized Container. Do not pierce or burn, even after use.
Wash thoroughly after handling.
Wear eye protection.

Response

IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical attention.



Safety Data Sheet

STP Products Manufacturing Company

44 Old Ridgebury Road
Suite 300
Danbury, CT 06810
Tel. 1-203-205-2900

3. Composition/Information on Ingredients

Component	CAS No.	Amount
1,1-difluoroethane (Propellant)	75-37-6	10-30%
Isobutane (Propellant)	75-28-5	10-30%
Propane (Propellant)	74-98-6	5-10%
Ethanol	64-17-5	30-60%
Tertiary Butyl Alcohol	75-65-0	1-5%

The exact concentrations are a trade secret.

4. First Aid Measures

Inhalation: If symptoms of exposure develop, remove to fresh air. Seek medical attention if breathing problems or irritation persist.

Skin Contact: Wash exposed skin with soap and water. If skin irritation or redness develop, seek medical attention.

Eye Contact: Flush eyes with large amounts of water for 15 minutes. If irritation or other symptoms persist, seek medical attention.

Ingestion: Ingestion is not an expected route of exposure for aerosols. However, if large quantities are ingested, get medical assistance by calling an emergency room or poison control center. Never give anything by mouth to a person who is unconscious or drowsy.

Most Important Symptoms: Causes eye irritation. May cause mild skin irritation. Mists may cause mild respiratory irritation. Inhalation of high concentrations of difluoroethane may cause anesthetic effects and a feeling of euphoria. Prolonged overexposure may cause rapid breathing, headache, dizziness and narcosis.

Indication of Immediate Medical Attention/Special Treatment: None required under normal use conditions.

5. Firefighting Measures

Suitable (and Unsuitable) Extinguishing Media: Use water fog, alcohol foam, carbon dioxide or dry chemical. Cool fire exposed containers with water.

Specific Hazards Arising from the Chemical: Extremely flammable aerosol. Contents under pressure. Keep away from ignition source and open flames. Exposure of containers to heat and flames can cause them to rupture, often with violent force. Thermal decomposition may produce carbon monoxide, carbon dioxide and fluorine compounds.

Special Fire Fighting Procedures: Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water. Use shielding to protect against bursting cans.

6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures: Eliminate all sources of ignition. Ventilate area with explosion proof equipment. Wear appropriate protective clothing and equipment.

Methods and Materials for Containment and Clean-Up: Place leaking can in a pail in a well-ventilated area away



Safety Data Sheet

STP Products Manufacturing Company

44 Old Ridgebury Road
Suite 300
Danbury, CT 06810
Tel. 1-203-205-2900

from ignition sources until pressure has dissipated. Collect liquid using non-combustible absorbents and place into a suitable container for disposal.

Environmental Precautions: Prevent entry into storm sewers and waterways. Report spill as required by local and national regulations.

7. Handling and Storage

Precautions for Safe Handling: Avoid contact with eyes. Avoid prolonged contact with skin. Avoid breathing vapors or aerosols. Use with adequate ventilation. Keep away from heat, sparks, hot surfaces and open flames. No smoking in storage or product use area. Wash thoroughly with soap and water after handling. Keep out of the reach of children. Contents under pressure; do not puncture or incinerate containers.

Conditions for Safe Storage, Including any Incompatibilities: Store in a cool, well-ventilated area, away from incompatible materials. Do not store in direct sunlight or above 120°F. **U.F.C. (NFPA 30B) Level 2 Aerosol.**

8. Exposure Controls / Personal Protection

Exposure Guidelines:

CHEMICAL	EXPOSURE LIMIT
Propane	1000 ppm TWA OSHA PEL
Isobutane	1000 ppm STEL ACGIH TLV
1,1-difluoroethane	1000 ppm AIHA WEEL
Ethanol	1000 ppm STEL ACGIH TLV 1000 ppm TWA OSHA PEL
Tertiary Butyl Alcohol	100 ppm TWA ACGIH TLV 100 ppm TWA OSHA PEL

Appropriate Engineering Controls: General ventilation should be adequate for normal use. For operations where the TLVs may be exceeded, forced ventilation such as local exhaust may be needed to maintain exposures below applicable limits. Use explosion proof equipment where required.

Personal Protective Equipment

Respiratory Protection: None under normal use conditions. For operations where the TLVs may be exceeded, a NIOSH approved respirator with an organic vapor cartridge and a dust/mist prefilter or supplied air respirator is recommended. Equipment selection depends on contaminant type and concentration. Select in accordance with 29 CFR 1910.134; all applicable laws and regulations; and good industrial hygiene practice.

Gloves: None under normal use conditions. Impervious gloves are recommended for prolonged or repeated skin contact.

Eye Protection: None under normal use conditions. Safety glasses are recommended to avoid eye contact.

Other Protective Equipment/Clothing: Appropriate protective clothing as needed to avoid prolonged or repeated skin contact.

9. Physical and Chemical Properties

Appearance and Odor: Clear water-thin liquid with fragrance in aerosol can.



Safety Data Sheet

STP Products Manufacturing Company

44 Old Ridgebury Road
Suite 300
Danbury, CT 06810
Tel. 1-203-205-2900

Physical State: Liquid-based aerosol	Odor Threshold: Not available
pH: Not applicable	Specific Gravity: ~0.785 (Liquid component)
Initial Boiling Point/Range: Not determined	Vapor Pressure: Not determined
Melting/Freezing Point: Not determined	Vapor Density: Not determined
Solubility In Water: Not determined	Percent Volatile: Not determined
Viscosity: Not determined	Evaporation Rate: Not determined
Relative Density: Not determined	VOC Content: Not determined
Coefficient Of Water/Oil Distribution: Not determined	Autoignition Temp: Not determined
Flash Point: < -58°F (-50°C) (1,1-difluoroethane- Propellant)	Flame extension: Not determined
Flammability Limits: LEL: 1.8% (Isobutane) UEL: 16.9% (1,1-difluoroethane)	Flammability (solid, gas): Propellant is flammable
Decomposition Temperature: Not available	

10. Stability and Reactivity

Reactivity: Not normally reactive.

Chemical Stability: Stable under normal storage and handling conditions.

Possibility of Hazardous Reactions: None known

Conditions to Avoid: Keep away from excessive heat, sparks and open flames. Containers may rupture at temperatures > 120°F (48.8°C).

Incompatible Materials: Strong oxidizing agents.

Hazardous Decomposition Products: Burning may produce carbon monoxide, carbon dioxide and fluorine compounds.

11. Toxicological Information

Potential Health Effects:

Acute Hazards:

Inhalation: Mist may cause mild irritation to the throat and respiratory tract. Inhalation of high concentrations of difluoroethane may cause anesthetic effects and a feeling of euphoria. Prolonged overexposure may cause rapid breathing. Headache, dizziness and narcosis.

Skin Contact: May cause mild skin irritation.

Eye Contact: Contact causes eye irritation with redness and tearing.

Ingestion: Ingestion is an unlikely route exposure for aerosol products. Swallowing may cause gastrointestinal disturbances.

Chronic Effects: None known

Carcinogenicity Listing: None of the components listed at 0.1% or greater is a carcinogen or potential carcinogen by IARC, NTP, ACGIH or OSHA

Numerical Measures of Toxicity:

Propane: LC50 Rat inhalation >800,000 ppm

Isobutane: LC50 Rat inhalation 658 mg/l/4 hr.



Safety Data Sheet

STP Products Manufacturing Company

44 Old Ridgebury Road
Suite 300
Danbury, CT 06810
Tel. 1-203-205-2900

1,1-difluoroethane: LC50 Inhalation Rat: > 437,500 ppm / 4 hr.
Ethanol: LD50 oral rat: 7060 mg/kg
LC50 inhalation rat 117 – 125 mg/L/ 4 hr.
Tertiary Butyl Alcohol: LD50 Oral Rat: 2,743 mg/kg
LD50 Skin Rabbit: >2,000 mg/kg
LC50 Inhalation Rat: > 10,000 ppm /4 hr.

12. Ecological Information

Ecotoxicity: No ecotoxicity data is currently available for product.

Ethanol: LC50 Fathead Minnow 14,200 mg/L/96 hr.
EC50: Daphnia Magna: 9268-14221 mg/L/48 hr.
EC50 Chlorella pyrenoidosa (Green algae; growth inhibition) 9310 mg/L/48 hr.
Tertiary Butyl Alcohol: LC50 Fathead Minnow >961 mg/L/96 hr.

Persistence and Degradability: No data available for product.

Ethanol: Readily biodegradable

Bio accumulative Potential: No data available for product.

Ethanol: Not expected to bio-accumulate

Mobility in Soil: No data available for product.

Ethanol: Highly mobile in soil

Other Adverse Effects: No data available

13. Disposal Considerations

Dispose of in accordance with all local, state/provincial and federal regulations. Offer empty containers for recycling.

14. Transport Information

DOT Hazardous Materials Description: UN1950, Aerosols, Class 2.1, Ltd Qty

IMDG Dangerous Goods Description: UN1950, Aerosols, 2.1, Ltd Qty

15. Regulatory Information

United States:

EPA TSCA INVENTORY: All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

CERCLA Section 103: This product has no RQ. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA Hazard Category (311/312): Classified under OSHA Hazcom 2012 GHS as per Section 2 of this SDS.



Safety Data Sheet

STP Products Manufacturing Company

44 Old Ridgebury Road
Suite 300
Danbury, CT 06810
Tel. 1-203-205-2900

SARA 313: This product contains the following chemicals subject to Annual Release Reporting Requirements under SARA Title III, Section 313 (40 CFR 372): None

Canada:

Canadian Environmental Protection Act: All of the ingredients are listed on the Canadian DSL.

16. Other Information

NFPA Rating (NFPA 704):	Health: 2	Fire: 4	Instability: 0
HMIS Rating:	Health: 2	Fire: 3	Physical Hazard: 0

REVISION DATE: 07/24/2018

REVISION SUMMARY: New SDS.

DATE OF PREVIOUS REVISION: N/A

DATA SUPPLIED IS FOR USE ONLY IN CONNECTION WITH OCCUPATIONAL SAFETY AND HEALTH